

CLASS FLANGES BOLT TORQUE LOADS

CLASS 150 – FLANGE INFORMATION

Nom. Flg. Size Ins. (mm)	Bolting No. x Dia. ins	A/F Ins.	Torque lbf.ft (Nm)	
			Bolt Lubricant Copperslip ($\mu=0.1$)	Bolt Lubricant Molycote 1000 ($\mu=0.13$)
1/2 (15)	4 x 1/2	7/8	20 (30)	25 (35)
3/4 (20)	4 x 1/2	7/8	25 (35)	30 (40)
1 (25)	4 x 1/2	7/8	30 (40)	35 (50)
1-1/2 (40)	4 x 1/2	7/8	40 (55)	50 (70)
2 (50)	4 x 5/8	1-1/16	75 (100)	95 (130)
3 (80)	4 x 5/8	1-1/16	75 (100)	95 (130)
4 (100)	8 x 5/8	1-1/16	75 (100)	95 (130)
6 (150)	8 x 3/4	1-1/4	120 (165)	150 (205)
8 (200)	8 x 3/4	1-1/4	120 (165)	150 (205)
10 (250)	12 x 7/8	1-7/16	175 (240)	220 (300)
12 (300)	12 x 7/8	1-7/16	180 (245)	230 (310)
14 (350)	12 x 1	1-5/8	295 (400)	370 (500)
16 (400)	16 x 1	1-5/8	240 (325)	300 (405)
18 (450)	16 x 1-1/8	1-13/16	415 (565)	520 (705)
20 (500)	20 x 1-1/8	1-13/16	415 (565)	520 (705)
24 (600)	20 x 1-1/4	2	575 (780)	725 (985)
30 (750)	28 x 1-1/4	2	360 (490)	455 (615)
36 (900)	32 x 1-1/2	2-3/8	630 (855)	800 (1085)
42 (1070)	36 x 1-1/2	2-3/8	-	-
48 (1220)	44 x 1-1/2	2-3/8	-	-

Flange Rating: ANSI B16.5, Class 150

Flange Materials: ASTM A105, ASTM A182 grades F50 and F51, ASTM A350 grades LF2 and LF3, ASTM A694 grade F52

Bolting Materials: ASTM A193 grades B7 and B7M, ASTM A320 grades L7, L7M and L43

Gasket Type: Compressed Asbestos Fibre

Service Temperature Range: Minus 101 thru' plus 400°C (Per Piping Class)

CLASS 300 – FLANGE INFORMATION

Nom. Flg. Size Ins. (mm)	Bolting No. x Dia. ins	A/F Ins.	Torque lbf.ft (Nm)	
			Bolt Lubricant Copperslip ($\mu=0.1$)	Bolt Lubricant Molycote 1000 ($\mu=0.13$)
1/2 (15)	4 x 1/2	7/8	20 (30)	30 (40)
3/4 (20)	4 x 5/8	1-1/16	40 (55)	50 (70)
1 (25)	4 x 5/8	1-1/16	45 (60)	55 (75)
1-1/2 (40)	4 x 3/4	1-1/4	85 (115)	105 (145)
2 (50)	8 x 5/8	1-1/16	55 (75)	70 (95)
3 (80)	8 x 3/4	1-1/4	120 (165)	150 (205)
4 (100)	8 x 3/4	1-1/4	120 (165)	150 (205)
6 (150)	12 x 3/4	1-1/4	120 (165)	150 (205)
8 (200)	12 x 7/8	1-7/16	190 (260)	240 (325)
10 (250)	16 x 1	1-5/8	320 (435)	405 (550)
12 (300)	16 x 1-1/8	1-13/16	450 (610)	565 (765)
14 (350)	20 x 1-1/8	1-13/16	355 (480)	450 (610)
16 (400)	20 x 1-1/4	2	435 (590)	550 (745)
18 (450)	24 x 1-1/4	2	490 (665)	620 (840)
20 (500)	24x 1-1/4	2	575 (780)	725 (983)
24 (600)	24x 1-1/2	2-3/8	785 (1065)	995 (1350)
30 (750)	28 x 1-3/4	2-3/4	1210 (1640)	1545 (2095)
36 (900)	32 x 2	3-1/8	1820 (2465)	2325 (3150)
42 (1070)	32 x 1-5/8	2-9/16	-	-
48 (1220)	32 x 1-7/8	2-15/16	-	-

Flange Rating: ANSI B16.5, Class 300

Flange Materials: ASTM A105, ASTM A182 grades F50 and F51, ASTM A350 grades LF2 and LF3, ASTM A694 grade F52

Bolting Materials: ASTM A193 grades B7 and B7M, ASTM A320 grades L7, L7M and L43

Gasket Type: Spiral Wound and Ring Joint

Service Temperature Range: Minus 101 thru' plus 400°C (Per Piping Class)

CLASS 600 – FLANGE INFORMATION

Nom. Flg. Size Ins. (mm)	Bolting No. x Dia. ins	A/F Ins.	Torque lbf.ft (Nm)	
			Bolt Lubricant Copperslip ($\mu=0.1$)	Bolt Lubricant Molycote 1000 ($\mu=0.13$)
1/2 (15)	4 x 1/2	7/8	20 (30)	30 (40)
3/4 (20)	4 x 5/8	1-1/16	40 (55)	50 (70)
1 (25)	4 x 5/8	1-1/16	45 (60)	60 (80)
1-1/2 (40)	4 x 3/4	1-1/4	105 (145)	130 (175)
2 (50)	8 x 5/8	1-1/16	75 (100)	95 (130)
3 (80)	8 x 3/4	1-1/4	120 (165)	150 (205)
4 (100)	8 x 7/8	1-7/16	195 (265)	245 (335)
6 (150)	12 x 1	1-5/8	320 (435)	405 (550)
8 (200)	12 x 1-1/8	1-13/16	470 (635)	590 (800)
10 (250)	16 x 1-1/4	2	575 (780)	725 (980)
12 (300)	20 x 1-1/4	2	575 (780)	725 (980)
14 (350)	20 x 1-3/8	2-3/16	695 (940)	880 (1190)
16 (400)	20 x 1-1/2	2-3/8	885 (1200)	1120 (1515)
18 (450)	20 x 1-5/8	2-9/16	1295 (1755)	1645 (2230)
20 (500)	24 x 1-5/8	2-9/16	1295 (1755)	1645 (2230)
24 (600)	24 x 1-7/8	2-15/16	1850 (2505)	2360 (3200)
30 (750)	28 x 2	3-1/8	2185 (2960)	2790 (3780)
36 (900)	28 x 2-1/2	3-7/8	3710 (5030)	4755 (6445)
42 (1070)	28 x 2-1/2	3-7/8	-	-
48 (1220)	32 x 2-3/4	4-1/4	-	-

Flange Rating: ANSI B16.5, Class 600

Flange Materials: ASTM A105, ASTM A182 grades F50 and F51, ASTM A350 grades LF2 and LF3, ASTM A694 grades F52 and F60

Bolting Materials: ASTM A193 grades B7 and B7M, ASTM A320 grades L7, L7M and L43

Gasket Type: Spiral Wound and Ring Joint

Service Temperature Range: Minus 101 thru' plus 400°C (Per Piping Class)



Hands Free Flange Backing Tools

Free demonstration CD available



Pneumatic Torque Wrenches



Hydraulic Torque Wrenches

Available from W. Christie.
Visit WWW.WCHRISTIE.COM
for further information

CLASS FLANGES BOLT TORQUE LOADS

CLASS 900 – FLANGE INFORMATION

Nom. Flg. Size Ins. (mm)	Bolting No. x Dia. ins	A/F Ins.	Torque lbf.ft (Nm)	
			Bolt Lubricant Copperslip (μ=0.1)	Bolt Lubricant Molycote 1000 (μ=0.13)
1/2 (15)	4 x 3/4	1-1/4	65 (90)	80 (110)
3/4 (20)	4 x 3/4	1-1/4	85 (115)	105 (145)
1 (25)	4 x 7/8	1-7/16	140 (190)	175 (240)
1-1/2 (40)	4 x 1	1-5/8	225 (305)	285 (390)
2 (50)	8 x 7/8	1-7/16	150 (205)	190 (260)
3 (80)	8 x 7/8	1-7/16	195 (265)	245 (335)
4 (100)	8 x 1-1/8	1-13/16	375 (505)	470 (635)
6 (150)	12 x 1-1/8	1-13/16	415 (560)	525 (710)
8 (200)	12 x 1-3/8	2-3/16	675 (915)	860 (1165)
10 (250)	16 x 1-3/8	2-3/16	675 (915)	860 (1165)
12 (300)	20 x 1-3/8	2-3/16	735 (995)	930 (1260)
14 (350)	20 x 1-1/2	2-3/8	935 (1265)	1185 (1605)
16 (400)	20 x 1-5/8	2-9/16	1295 (1755)	1645 (2230)
18 (450)	20 x 1-7/8	2-15/16	1850 (2505)	2360 (3200)
20 (500)	20 x 2	3-1/8	2245 (3040)	2865 (3885)
24 (600)	20 x 2-1/2	3-7/8	4190 (5680)	5370 (7280)
30 (750)	20 x 3	4-5/8	7070 (9585)	9085 (12315)
36 (900)	20 x 3-1/2	5-3/8	10935 (14825)	14065 (19070)

Flange Rating: ANSI B16.5, Class 900

Flange Materials: ASTM A105, ASTM A182 grades F50 and F51, ASTM A350 grades LF2 and LF3, ASTM A694 grades F52 and F60

Bolting Materials: ASTM A193 grades B7 and B7M, ASTM A320 grades L7, L7M and L43

Gasket Type: Spiral Wound and Ring Joint

Service Temperature Range: Minus 101 thru' plus 400°C (Per Piping Class)

CLASS 1500 – FLANGE INFORMATION

Nom. Flg. Size Ins. (mm)	Bolting No. x Dia. ins	A/F Ins.	Torque lbf.ft (Nm)	
			Bolt Lubricant Copperslip (μ=0.1)	Bolt Lubricant Molycote 1000 (μ=0.13)
1/2 (15)	4 x 3/4	1-1/4	65 (90)	80 (110)
3/4 (20)	4 x 3/4	1-1/4	85 (115)	105 (145)
1 (25)	4 x 7/8	1-7/16	140 (190)	175 (240)
1-1/2 (40)	4 x 1	1-5/8	260 (350)	330 (445)
2 (50)	8 x 7/8	1-7/16	160 (215)	200 (270)
3 (80)	8 x 1-1/8	1-13/16	395 (535)	500 (675)
4 (100)	8 x 1-1/4	2	575 (780)	730 (990)
6 (150)	12 x 1-3/8	2-3/16	770 (1040)	980 (1325)
8 (200)	12 x 1-5/8	2-9/16	1295 (1755)	1645 (2230)
10 (250)	12 x 1-7/8	2-15/16	2000 (2710)	2550 (3455)
12 (300)	16 x 2	3-1/8	2125 (2880)	2710 (3670)
14 (350)	16 x 2-1/4	3-1/2	3040 (4120)	3890 (5270)
16 (400)	16 x 2-1/2	3-7/8	4190 (5680)	5370 (7280)
18 (450)	16 x 2-3/4	4-1/4	5585 (7570)	7170 (9720)
20 (500)	16 x 3	4-5/8	7280 (9870)	9350 (12675)
24 (600)	16 x 3-1/2	5-3/8	11600 (1570)	14920 (20230)

Flange Rating: ANSI B16.5, Class 1500

Flange Materials: ASTM A105, ASTM A182 grades F50 and F51, ASTM A350 grades LF2 and LF3, ASTM A694 grades F52, F60 and F65

Bolting Materials: ASTM A193 grades B7 and B7M, ASTM A320 grades L7, L7M and L43

Gasket Type: Spiral Wound and Ring Joint

Service Temperature Range: Minus 101 thru' plus 400°C (Per Piping Class)

CLASS 2500 – FLANGE INFORMATION

Nom. Flg. Size Ins. (mm)	Bolting No. x Dia. ins	A/F Ins.	Torque lbf.ft (Nm)	
			Bolt Lubricant Copperslip (μ=0.1)	Bolt Lubricant Molycote 1000 (μ=0.13)
1/2 (15)	4 x 3/4	1-1/4	95 (130)	120 (165)
3/4 (20)	4 x 3/4	1-1/4	120 (165)	150 (205)
1 (25)	4 x 7/8	1-7/16	210 (285)	265 (360)
1-1/2 (40)	4 x 1-1/8	1-13/16	470 (635)	590 (800)
2 (50)	8 x 1	1-5/8	320 (435)	405 (550)
3 (80)	8 x 1-1/4	2	650 (880)	820 (1110)
4 (100)	8 x 1-1/2	2-3/8	1060 (1435)	1350 (1830)
6 (150)	8 x 2	3-1/8	2425 (3285)	3100 (4200)
8 (200)	12 x 2	3-1/8	2425 (3285)	3100 (4200)
10 (250)	12 x 2-1/2	3-7/8	4190 (5680)	5370 (7280)
12 (300)	12 x 2-3/4	4-1/4	6385 (8655)	8195 (11110)

Flange Rating: ANSI B16.5, Class 2500

Flange Materials: ASTM A105, ASTM A182 grades F50 and F51, ASTM A350 grade LF2

Bolting Materials: ASTM A193 grades B7 and B7M, ASTM A320 grades L7, L7M and L43

Gasket Type: Spiral Wound and Ring Joint

Service Temperature Range: Minus 101 thru' plus 400°C (Per Piping Class)

SALE AND HIRE AVAILABLE

C-RAD Pneumatic Torque Multipliers, Battery Torque Multipliers,
Electric Torque Multipliers, Hydraulic Torque Wrenches,
Powered & Hand Pump Units, Offset Gearboxes, Customised Products,
Impact Sockets & Accessories, Bolt Testing Facility, Repair & Calibration Workshop

CHRISTIES SOLVE YOUR PROBLEMS AND OFFER TORQUE SOLUTIONS

No statement or data herein is warranted or guaranteed to be accurate

W.CHIRSTIE (INDUSTRIAL) LTD
CHRISTIE HOUSE, MEADOWBANK ROAD, ROTHERHAM, SOUTH YORKSHIRE, S61 2NF, UK
T: +44(0)1709 550088 F: +44(0)1709 550030
E: INFO:WCHRISTIE.COM W: WWW.WCHRISTIE.COM

REGISTERED OFFICE: UNIT F7, FESTIVAL BUSINESS CENTRE, 150 BRAND STREET, GLASGOW, G51 1DH, SCOTLAND
T: +44(0)141 427 9801 F: +44(0)141 427 9802
E: WCHRISTIEGLW@BTCONNECT.COM W: WWW.WCHRISTIE.COM
REGISTRATION No: SC 035247