




MANUAL TORQUE MULTIPLIER HT2-5:1 – TECHNICAL DATA



MANUAL TORQUE MULTIPLIER HT2-5:1 – TECHNICAL DATA

DESCRIPTION

The Christie Manual Torque Multiplier HT2-5:1 employs multiple stages of epicyclic gearing to give a accurate torque output and ratio.

Ratio quoted is the torque multiplication ratio, not the velocity ratio as given for some competitor's products. For example, the velocity ratio may be 5.454:1 to give a torque multiplication of 5:1 +/-4%.

The reaction force works in the opposite direction to the applied torque. The point of reaction should be kept as far away as practicable from the centre of the square drive to minimise this force.

Where the standard reaction plate is not suitable, it may be possible to adapt it. Please contact W. Christie (Industrial) Limited for assistance.

The HT2-5:1 must always be used with the following:-

- Impact Quality Sockets
- Reaction Arm
- Manual Torque Wrench

SPECIFICATION

Part Number:	16012
Input Square:	3/4" Female (19.05mm)
Output Square:	1" Male (25.4mm)
Direction:	Forward / Reverse
Torque Accuracy:	+/- 4%
Torque Ratio:	5:1
Velocity Ratio:	5.454:1
Minimum Output Torque:	170 Nm (125 lbf.ft)
Maximum Output Torque:	1,700 Nm (1,250 lbf.ft)
Maximum Input Speed:	42 rpm
Tool Weight:	3 Kg (6.62 lbs)
Reaction Plate Weight:	2.2 Kg (4.86 lbs)

ACCESSORIES AVAILABLE

The following accessories are available upon request and can be custom made to suit requirements. Please contact W. Christie (Industrial) Limited for more information:-

- Electronic Torque Transducers (For Precise Torque Monitoring)
- Manual Torque Wrench
- Special Reactions
- Impact Quality Sockets
- Torque Checking System (Rundown Fixture)

No statement or data within this literature is warranted or guaranteed to be accurate.



W. CHRISTIE (INDUSTRIAL) LTD
CHRISTIE HOUSE
MEADOWBANK ROAD
ROTHERHAM
SOUTH YORKSHIRE
S61 2NF UK
T: +44(0)1709 550088 F: +44(0)1709 550030
E: INFO@WCHRISTIE.COM W: WWW.WCHRISTIE.COM